

# TECHNICAL SPECIFICATIONS

# EOS C300 Mark III

## ACCESSORIES

### Supplied

Camera Grip GR-V1, Thumb rest, Mic holder unit [w/ M4 screw], LCD Monitor LM-V2, LCD Attachment Unit LA-V2, Handle unit, Shoulder strap SS-1200, Battery Charger CG-A20, Compact power adapter CA-CP200B, AC cable, Battery pack (BP-A60), Extension System Attachment Bracket, Unit Cable UN-5, Other: Stopper, Hex Wrenches (M4 and M3), Hex Socket Head Bolt (1/4 in.), Hex Socket Head Bolt (M3)

### Optional

Canon Battery Pack BP-A30/BP-A60 (provided with camera)  
 Canon Battery Charger CG-A10/CG-A20 (provided with camera)  
 Canon Remote Controller RC-V100  
 Canon Compact Power Adapter CA-CP200B (provided with camera)  
 Canon Shoulder Strap SS-1200 (provided with camera)  
 Canon Tripod base TB-1  
 Canon Wireless Transmitter WFT-E9\*  
 Canon GPS Receiver GP-E2  
 Canon Unit Cable UN-5 (provided)/UN-10 (purchased separately)  
 Canon OLED Electronic View Finder EVF-V50/EVF-V70  
 Canon Extension unit 1: EU-V1  
 Canon Extension unit 2: EU-V2  
 Canon EF Cinema Lock Mount Kit CM-V1  
 Canon PL Mount Kit PM-V1  
 Canon B4 Mount Adapter MO-4E/MO-4P  
 Canon LCD Monitor LM-V2 (included)/LM-V1  
 Canon LCD Attachment Unit LA-V2 (included)/LA-V1  
 Canon Camera Grip GR-V1 (included)  
 Canon Shoulder Support Unit SU-15  
 Canon Shoulder Style Grip Unit SG-1  
 Canon Clamp Base CL-V2  
 Canon Rod Clamp RD-1  
 Canon Handle Unit HDU-2  
 Canon 8-pin Remote Cable RR-10/RR-100  
 Canon EF/EF cinema lens group,  
 Canon PL cinema lens group, and accessories designed for these lenses  
 (\*) New products

### Third Party Accessories

V-Lock battery (via EU-V2 module)

## MISCELLANEOUS

### Dimensions (Main Body Only)

### Weight (Body Only)

### Weight (accessories)

153x148x168mm (WxHxD)

Approx. 1,750g

Extension unit 1: EU-V1: Approx. 114g

Extension unit 2: EU-V2: Approx. 652g

OLED Electronic View Finder: EVF-V50: Approx. 170g

EF Cinema Lock Mount Kit CM-V1:

Approx. 170g \*Not including cap

PL Mount Kit PM-V1:

Approx. 345g \*Not including cap

MO-4E: Approx. 230g MO-4P: Approx. 248g

CFexpress card: Approx. 8g (0.28 oz.)

Clamp Base: CL-V2: Approx. 120g (4.2 oz.)

Approx. 0 to 40°C, (85% relative humidity)

Approx. -5 to 45°C, (60% relative humidity)

BP-A60 (Supplied), BP-A30 (Optional) V-Lock

with EU-V2, 11V - 20V, Mains 4-pin XLR

RAW:

Super 35mm 1 Gbps 4096x2160, 31.0W

Super 16mm 250Mbps, 28.7W

XF-AVC:

Super 35mm 810Mbps 4096x2160, 31.0W

Super 16mm 310Mbps, 28.7W

Max. power consumption 63 W

RAW/XF-AVC

Super 35mm: 130 minutes

Super 16mm: 140 minutes

via BP-A60 battery

### Operating Temperature range

### Power Supply

### Power Consumption

### Recording Time

\* All specifications are subject to change without notice

### Footnotes

Canon is an authorized licensee of the CFexpress Ver.2.0™ trademark owned by CompactFlash Association, which may be registered in various jurisdictions.

Live for the story\_

Canon Inc.  
 canon.com  
 Canon Europe  
 canon-europe.com  
 English edition  
 Canon Europa NV 2020